



# ***Elec-Trak***<sup>®</sup>

**Tractor**

## **E8M FACTS**



### **FEATURES**

- 8 horsepower class tractor — not a rider
- Elec-Trak tractor safety features
  - Seat switch-instant off
  - "return-to-off" system
  - Start only with clutch disengaged
- Excellent maneuverability and good stability
- Simple, feather-touch clutch control and brake in one pedal
- Three speeds forward — one reverse
- Large disk brake
- One piece welded-unitized body frame
- Fast acting lever lift for attachments
- Large rear storage area/weight box
- Super performance 36" rotary mower
  - Direct, independent motor-blade drive
  - Three second blade stop
  - Side discharge
  - Independent ground-following suspension
- Front tires 5:00 x 6    Rear 6:50 x 8
- Mower easy to remove and install
- Width 35"; length 67", weight 495 pounds
- 4 mph maximum speed

**GENERAL  ELECTRIC**



# ***Elec-Trak***<sup>®</sup>

**Tractor**

## **E8M FACTS**

### **PERFORMANCE**

#### **Mowing:**

36" side discharge rotary mower for 1-1/4 acre mowing range per charge.

#### **Hauling:**

Built-in pin hitch to handle tough towing jobs.

**Optional 36-volt outlet for  
Elec-Trak hand tools.**

#### **Snow Removal:**

Handles 42" snow/dozer blade.

— Plows 1-2 hours in average 6-12 inch snow.

### **BUILT-IN BATTERY RECHARGE**

(from standard 110V, 15 amp household outlet)

85% recharge	Approx. 5 hours*
70% recharge	Approx. 3 1/2 hours
40% recharge	Approx. 2 hours

\*(Charger runs longer for full battery equalization).

### **WARRANTY SUMMARY (for residential use)**

In addition to a one year warranty against defects on all tractor parts, the E8M Elec-Trak tractor features a three-year battery warranty. The battery is warranted against defects for the first year, with a pro rata charge during the next two years on the E8M Elec-Trak tractor. See E8M Owner's Use and Care Manual for complete warranty statement.

General Electric Company  
Outdoor Power Equipment Operation  
Corporations Park, Bldg. 702  
Schenectady, N.Y. 12345

---

**GENERAL  ELECTRIC**